

GLIDETECH[®] DROP HOSE



APPLICATION: Tank truck delivery drop hose. Extra flexible, light weight, low drag resistance makes the hose easy to handle. Suitable for oil and petrol, aromatic content up to 50%.

DESCRIPTION

Tube NBR compound, black, smooth
Reinforcement synthetic plies, steel wire helices
Cover wide corrugated, black, special polymer highly ozone resistant, aging and abrasion resistant, cover with low friction rate, conductive

TECHNICAL CHARACTERISTICS

Temperature range -22°F/212°F (-30°C / +100°C)
Vacuum 19 Inch HG (0.5 bar)
Norm ISO 1307 for dimensional tolerances

Inside diameter		Outside diameter	Working pressure		Burst pressure		Appr. weight		Bending radius	
[mm]	[in]	[in]	[bar]	[psi]	[bar]	[psi]	[kg/mt]	[lbs/ft]	[mm]	[in]
25	1	1.46	10	150	30	450	0,88	.59	25	1
38	1 ½	2.00	10	150	30	450	1,12	.75	38	1.5
51	2	2.52	10	150	30	450	1,56	1.05	51	2
63,5	2 ½	3.09	10	150	30	450	2,18	1.46	63,5	2.5
76	3	3.62	10	150	30	450	2,56	1.72	76	3
102	4	4.65	9	135	27	405	3,32	2.22	102	4

Data refers to ambient temperature 68°F (20°C)
 Other diameters available on request.



tuderhose@crpindustries.com
 www.crpudertechnica.com

35 Commerce Drive
 Cranbury, NJ 08512
 Tel. (800)526-4066